



AMERICAN COATINGS

TC 48

APPLICATION INFORMATION

Do not apply if temperatures are below 50° F or humidities above 85 percent.

APPLICATION METHOD

Airless spray preferred, but can be brushed or troweled. Special spray equipment can be used on large jobs to get away from short pot life problems. See your American Coatings Representative for more details.

MIXING

Thoroughly mix MEKP catalyst into part A before application.

CLEAN-UP AND THINNING

Do not thin this product. Clean up with American Coatings TH 315 thinner.

SPRAY EQUIPMENT

FOR AIRLESS SPRAY

Pump Ratio -----	30:1
Air Supply (in) -----	100 psi
Hose Diameter (ID) -----	1/4"
Hose Length -----	75'
Tip Size (in) -----	.065"

SAFETY INFORMATION

WARNING! FLAMMABLE, HARMFUL IF INHALED, CAUSES IRRITATION

Keep away from sparks or flame. Vapors may cause flash fire. Use with adequate ventilation. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator during and after applications unless air monitoring demonstrates vapor/mist levels are below applicable limits. Avoid contact with peroxide catalyst or prolonged skin contact with vinyl ester resin. Contains styrene monomer.

SHIPPING DATA

Proper Shipping Name -----	Oxidizing Matt Paint Liquid
Hazard Class-----	Methyl Ethyl Ketone Peroxide Flammable Liquid Oxidizer
Flash Pt. °F SETA -----	88° F Part A Oxidizer Part B
UN No.-----	1263

PACKAGING

<u>Shipping Wt.</u>	<u>PART A</u>	<u>PART B</u>
	Fives 52.5 lbs.	Pints 7.33 oz.



AMERICAN COATINGS

DISCLAIMER

The facts stated and the recommendations and suggestions herein are based upon experiments and supplier information believed to be reliable. No guarantee is made of their accuracy, however, and American Coatings ASSUMES NO LIABILITY FOR PRODUCT FAILURE OTHER THAN TO SUPPLY REPLACEMENT MATERIAL FOR PRODUCTS SHOWN TO BE DEFECTIVE WHEN DELIVERED OR TO REFUND THE PURCHASE PRICE. Except as stated, THERE ARE NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. AMERICAN COATINGS SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL AND CONSEQUENTIAL DAMAGES. No statement contained herein shall be constructed as an inducement to infringe existing patents or as an endorsement of specific manufacturers.

revised 10/06